



Bernad[®]
equipamiento industria alimentaria

STAINLESS STEEL TILTING ARM 2 M

Stainless steel tilting arm for dispatch, quartering and truck loading

STAINLESS STEEL

DISPATCH

TWIN-RAIL

TRUCK LOADING



DESCRIPTION

Tilting arm designed to make dispatch, quartering and truck loading easier in meat plants. It integrates into the twin-rail overhead conveyor system and is operated by a hoist.

Built in stainless steel, with stainless steel swivel joint and end stop. Designed to be operated with a 250 or 500 kg hoist.

CONSTRUCTION AND STANDARD EQUIPMENT

- Stainless steel structure
- Stainless steel swivel joint and end stop
- Operated with a 250 or 500 kg hoist
- Length: 2 m

KEY DATA

Material	Stainless steel	Swivel joint	Stainless steel	End stop	Stainless steel
Operation	Hoist	Hoist	250 or 500 kg	Length	2 m

MODELS AND DIMENSIONS

REF.	CONFIGURATION	LENGTH	SUITABLE FOR
245125302	Stainless tilting arm	2 m	250/500 kg hoist

Custom manufacturing on request. Compatible with the Bernad twin-rail overhead conveyor system.

APPLICATIONS

Dispatch docks, quartering and truck loading in slaughterhouses and meat plants.

For information only. Specifications, dimensions and finishes may change without notice due to product improvements. The image is indicative. Please request a quotation to confirm dimensions, materials and lead times.