TWIN-RAIL OVERHEAD TRACK

Extruded aluminium twin-rail track for overhead conveying, in 4 m bars

ALUMINIUM | TWIN-RAIL | TRACK | MEAT INDUSTRY



DESCRIPTION

Extruded aluminium twin-rail track, the basis of the Bernad® twin-rail overhead conveyor system for moving carcasses and cuts. Trolleys run on it, and curves, switches and rail brackets connect to it.

Made of 6063-53 Ho alloy. Sold per linear metre and supplied in 4-metre bars.

CONSTRUCTION AND STANDARD EQUIPMENT

- Extruded aluminium, 6063-53 Ho alloy
- Supplied in 4 m bars
- Sold per linear metre, in multiples of 2
- Core of the system: trolleys, curves and switches

KEY DATA					
Material	**Aluminium**	Alloy	**6063-53 Ho**	Process	**Extrusion**
Type	**Twin-rail**	Bar length	**4 m**	Sales multiple	**2**

MODELS AND DIMENSIONS

REF.	CONFIGURATION	LENGTH	SUITABLE FOR
245000025	Twin-rail track, bar	**4 m**	Twin-rail system

Supplied in 4 m bars. Compatible with the entire Bernad twin-rail overhead conveyor system.

APPLICATIONS

Slaughterhouses, cutting rooms, cold rooms and meat processing plants with twin-rail overhead systems.

For information only. Specifications, dimensions and finishes may change without notice due to product improvements. The image is indicative. Please request a quotation to confirm dimensions, materials and lead times.

José Bernad, S.L.
Parque Empresarial Campollano, Avda. Adeca 17 — 02007 Albacete (España)
www.josebernad.com
T: +34 967 219 649