



Bernad[®]
equipamiento industria alimentaria

ADA PRECISION BALANCE

220 to 620 g precision balance with 1 mg readability and draught shield, below-balance weighing and RS232

1 MG

220 TO 620 G

TARGET WEIGHT

RS232



DESCRIPTION

The ADA is a load-cell precision balance of 220 to 620 g with 1 mg readability, with a roomy draught shield for samples.

Backlit LCD with 15 mm digits, stainless pan, external calibration, buzzer and below-balance weighing. Works in grams, ounces, carats and pennyweight.

RS232 output and mains adapter; counting, percentage and target-weight (checkweighing) functions.

CONSTRUCTION AND STANDARD EQUIPMENT

- Load cell; external calibration
- Ø115 mm stainless pan; draught shield
- 15 mm backlit LCD; buzzer
- Below-balance weighing and RS232 output

KEY DATA

Capacity	220 to 620 g	Readability	1 mg	Class	II
Calibration	External	Pan	Ø115 mm	Output	RS232

VERSIONS

REF.	CAPACITY (G)	DIVISION (G)	CLASS	CALIBRATION	LEGAL FOR TRADE
261361	220	0.001	II	External	No
261362	420	0.001	II	External	No
261363	620	0.001	II	External	No

Baxtran references. Other configurations on request.

APPLICATIONS

Laboratories, quality control, pharmacy, jewellery, education, research and workshops that need high-precision weighing.

For information only. Specifications, dimensions and finishes may change without notice due to product improvements. The image is indicative. Please request a quotation to confirm dimensions, materials and lead times.