



Bernad[®]
equipamiento industria alimentaria

BAP PRECISION BALANCE

Legal-for-trade class II precision balance from 300 to 3,000 g with 48 h battery and density calculation

CLASS II

48 H BATTERY

RS232

LEGAL FOR TRADE



DESCRIPTION

The BAP is a load-cell precision balance, class II, from 300 to 3,000 g with readability from 5 mg, legal for trade.

Backlit 6-digit 15 mm LCD, ABS housing, stainless pan, external calibration, 4 adjustable feet and spirit level and below-balance weighing for density determination.

48-hour internal battery, mains adapter and RS232 output for PC or GODEX label printer.

CONSTRUCTION AND STANDARD EQUIPMENT

- Backlit 6-digit 15 mm LCD
- Stainless pan; ABS housing; external calibration
- 48 h internal battery
- RS232 output; below-balance weighing

KEY DATA

Capacity	300 to 3,000 g	Division	0.005 to 0.05 g	Class	II
Calibration	External	Battery	48 h	Output	RS232

VERSIONS

REF.	CAPACITY (G)	DIVISION (G)	CLASS	CALIBRATION	LEGAL FOR TRADE
261418	300	0.005	II	External	Yes
261419	600	0.01	II	External	Yes
261420	1,500	0.02	II	External	Yes
261421	3,000	0.05	II	External	Yes

Baxtran references. Other configurations on request.

APPLICATIONS

Laboratories, quality control, pharmacy, jewellery, education, research and workshops that need high-precision weighing.
Standards: Legal for trade, class II.

For information only. Specifications, dimensions and finishes may change without notice due to product improvements. The image is indicative. Please request a quotation to confirm dimensions, materials and lead times.