

BAR PRECISION BALANCE

Precision balance from 150 to 6,000 g with 48 h battery, RS232 and legal-for-trade versions

CLASS II

48 H BATTERY

RS232

150–6,000 G



DESCRIPTION

The BAR is a load-cell precision balance, class II, from 150 to 6,000 g with readings from 1 mg; two references are approved for legal-for-trade use.

Backlit 6-digit 15 mm LCD, ABS housing, stainless pan, external calibration, 4 adjustable feet and spirit level, with a draught shield on the 150, 300 and 600 g models.

48-hour internal battery, mains adapter and RS232 output for printer and PC.

CONSTRUCTION AND STANDARD EQUIPMENT

- Backlit 6-digit 15 mm LCD
- Stainless pan; ABS housing; external calibration
- 48 h internal battery
- RS232 output; draught shield (150-600 g)

KEY DATA

Capacity	150 to 6,000 g	Division	0.001 to 0.1 g	Class	II
Calibration	External	Battery	48 h	Output	RS232

VERSIONS

REF.	CAPACITY (G)	DIVISION (G)	LEGAL FOR TRADE	REF.	CAPACITY (G)	DIVISION (G)	LEGAL FOR TRADE
260103	150	0.001	No	260106	3,000	0.05	No
260105	300	0.005	No	260110	6,000	0.1	No
260109	600	0.01	No	260112	600	0.1 (CE-M)	Yes
260101	1,500	0.01	No	260111	6,000	1 (CE-M)	Yes
260100	1,500	0.02	No				

Baxtran references. Other configurations on request.

APPLICATIONS

Laboratories, quality control, pharmacy, jewellery, education, research and workshops that need high-precision weighing.
Standards: References 260112 and 260111 legal for trade; class II.

For information only. Specifications, dimensions and finishes may change without notice due to product improvements. The image is indicative. Please request a quotation to confirm dimensions, materials and lead times.