

BRT WEIGH BEAMS

Pair of 1,500 or 3,000 kg weigh beams in painted or stainless steel, without indicator

WEIGH BEAMS

1,500 / 3,000 KG

IN PAIRS

NO INDICATOR



DESCRIPTION

The BRT are weigh beams supplied in pairs to place under pallets, tanks, cages or structures and weigh them where they stand. Also in stainless steel with IP68 stainless load cells.

Height-adjustable feet, IP66 ABS junction box and 2 m of cable per beam to a single connector. Painted steel beams use IP67 nickel-plated steel OIML R-60 load cells.

There are legal-for-trade and non-legal references (see table). Supplied without indicator: combine it with the Baxtran weight indicator that best suits the job.

CONSTRUCTION AND STANDARD EQUIPMENT

- Pair of beams with adjustable feet
- IP67 nickel-plated steel OIML R-60 load cells (IP68 stainless on stainless beams)
- IP66 ABS junction box
- 2 m cable per beam with single connector

KEY DATA

Capacity	1,500 / 3,000 kg	Division	500 g / 1 kg	Length	1250 mm
Supplied as	Pair	Load cells	OIML R-60	Cable	2 m per beam

VERSIONS

REF.	CAPACITY (KG)	DIVISION (G)	MATERIAL	BEAM (MM)	LEGAL FOR TRADE
260206	1,500	500	Painted steel	1250 × 100	Yes
260207	1,500	500	Painted steel	1250 × 100	No
260208	3,000	1,000	Painted steel	1250 × 100	Yes
260209	3,000	1,000	Painted steel	1250 × 100	No
260210	1,500	500	Stainless steel	1250 × 100	Yes
260211	3,000	1,000	Stainless steel	1250 × 100	Yes

Supplied in pairs.

APPLICATIONS

Livestock, warehouses, industry and construction: weighing irregular or oversized loads without a fixed platform. Standards: References 260206, 260208, 260210 and 260211 legal for trade; OIML R-60 load cells.

For information only. Specifications, dimensions and finishes may change without notice due to product improvements. The image is indicative. Please request a quotation to confirm dimensions, materials and lead times.