

BVRS LOW-PROFILE PLATFORM

Low-profile stainless steel 4-load-cell platform with standard ramp, 600 to 3,000 kg, legal for trade

LOW PROFILE

RAMP INCLUDED

600–3,000 KG

STAINLESS



DESCRIPTION

The BVRS is a low-profile 4-load-cell platform placed on the floor with a standard access ramp: pallet trucks roll on without a pit.

Structure in 5 mm smooth stainless steel plate, ramp with floor-fixing plates, stainless steel OIML R-60 C3 IP67 load cells, IP66 ABS junction box and adjustable feet. Legal for trade.

From 600 kg on 800 × 800 mm to 3,000 kg on 1500 × 1500 mm. Supplied without indicator: combine it with the Baxtran weight indicator that best suits the job.

CONSTRUCTION AND STANDARD EQUIPMENT

- 5 mm smooth stainless steel plate
- Standard access ramp and floor fixing
- 4 stainless OIML R-60 C3 IP67 load cells
- IP66 ABS junction box; adjustable feet

KEY DATA

Capacity	600 to 3,000 kg	Division	200 g to 1 kg	Platform	800×800 to 1500×1500
Profile	Low	Ramp	Standard	Load cells	IP67

VERSIONS

PLATFORM (MM)	CAPACITY (KG)	DIVISION (G)	BAXTRAN REF.
800 × 800	600	200	261525
1000 × 1000	600 / 1,500	200 / 500	261526 / 261527
1200 × 1200	1,500 / 3,000	500 / 1,000	260246 / 260247
1500 × 1200	1,500 / 3,000	500 / 1,000	260248 / 260249
1500 × 1500	1,500 / 3,000	500 / 1,000	260250 / 260251

Baxtran references. Other configurations on request.

APPLICATIONS

Warehouses, dispatch, food industry and logistics: legal-for-trade pallet weighing with a pallet truck, no building work needed.
Standards: Legal for trade; OIML R-60 C3 load cells.

For information only. Specifications, dimensions and finishes may change without notice due to product improvements. The image is indicative. Please request a quotation to confirm dimensions, materials and lead times.