

HG PRECISION BALANCE

320 to 1,000 g precision balance with 1 mg readability and draught shield, metal structure and external or internal calibration

1 MG

320 TO 1,000 G

GLP/GMP

EXT./INT. CALIBRATION



DESCRIPTION

The HG is a 320 to 1,000 g precision balance with 1 mg readability and a draught shield, with a cast-metal structure that protects it from electrical storms and electromagnetic interference.

8-digit 15 mm LCD with advanced eye protection and guide messages, 7 direct keys, 128 × 128 mm stainless pan, 4 adjustable feet, spirit level, 2 to 3 second response and below-balance hook.

Versions with external or internal calibration, RS232 for PC and printer and GLP/GMP functions; dust cover and blister included.

CONSTRUCTION AND STANDARD EQUIPMENT

- Interference-proof cast-metal structure
- 128 × 128 mm stainless pan; draught shield
- 8-digit 15 mm LCD with eye protection
- RS232; external or internal calibration

KEY DATA

Capacity	320 to 1,000 g	Readability	1 mg	Class	II
Calibration	Ext. or int.	Response	2-3 s	Pan	128 × 128 mm

VERSIONS

REF.	CAPACITY (G)	DIVISION (G)	CLASS	CALIBRATION	LEGAL FOR TRADE
260342	320	0.001	II	External	No
260344	420	0.001	II	External	No
260340	1,000	0.001	II	External	No
260343	320	0.001	II	Internal	No
260345	420	0.001	II	Internal	No
260341	1,000	0.001	II	Internal	No

Baxtran references. Other configurations on request.

APPLICATIONS

Laboratories, quality control, pharmacy, jewellery, education, research and workshops that need high-precision weighing.
Standards: GLP/GMP functions.

For information only. Specifications, dimensions and finishes may change without notice due to product improvements. The image is indicative. Please request a quotation to confirm dimensions, materials and lead times.