

TRG IP68 STAINLESS SCALE

IP68 stainless single-load-cell scale from 30 to 300 kg, legal for trade

STAINLESS STEEL

IP68

30–300 KG

LEGAL FOR TRADE



DESCRIPTION

The TRG is the most watertight single-load-cell set in the range: platform, column and stainless steel IP68 load cell, plus a GI400 LCD IP68 indicator with 40 mm digits.

There are 6 capacity and pan combinations, from 30 kg on 305 × 335 mm to 300 kg on 500 × 650 mm, each in a general-use or legal-for-trade version. Load cells carry an OIML R-60 C3 test certificate.

Designed to be washed daily, it supports single range, multi-range or multi-interval, runs on 230 V and comes with 2 RS232 outputs for printer or PC, printing headers and totals.

CONSTRUCTION AND STANDARD EQUIPMENT

- Stainless steel tubular frame, pan and column
- Stainless steel IP68 load cell with OIML R-60 C3 certificate
- Backlit GI400 LCD IP68 indicator with 40 mm digits
- 230 V mains and 2 RS232 outputs as standard

KEY DATA

Capacity	30 to 300 kg	Division	5 to 100 g	Pan	305×335 to 500×650
Protection	IP68	Indicator	GI400 LCD 40 mm	Outputs	2 × RS232

VERSIONS

PAN (MM)	CAPACITY (KG)	DIVISION (G)	REF. GENERAL USE	CE-M DIVISION (G)	REF. LEGAL FOR TRADE
305 × 335	30	5	261214	10	261220
305 × 335	60	10	261215	20	261221
420 × 550	60	10	261216	20	261222
420 × 550	150	20	261217	50	261223
500 × 650	150	20	261218	50	261224
500 × 650	300	50	261219	100	261225

Baxtran references. Other configurations on request.

APPLICATIONS

Fishmongers, slaughterhouses, cutting rooms and processing plants with heavy washdown; legal-for-trade selling by weight. Standards: Legal for trade (versions with CE-M division); load cells with OIML R-60 C3 test certificate.

For information only. Specifications, dimensions and finishes may change without notice due to product improvements. The image is indicative. Please request a quotation to confirm dimensions, materials and lead times.