



Bernad[®]
equipamiento industria alimentaria

RPS220 SEMI-AUTOMATIC TRAY SEALER

Benchtop tray sealer with optional gas flushing and film trimming

BENCHTOP

SEMI-AUTOMATIC

TRAYS

GAS OPTION



DESCRIPTION

The RPS220 seals trays up to 260 × 195 mm and 120 mm deep. Gas flushing and perimeter film trimming are available as options.

When the mould is inserted, sealing starts automatically and the film advances by itself; the sealing cycle takes 2 to 3 seconds and an audible signal marks the end of the cycle.

Sealing is hygienic and leak-tight: contents cannot spill and do not release or absorb odours, product keeps better and presentation improves.

CONSTRUCTION AND STANDARD EQUIPMENT

- Digital panel with 9 programs and electronic temperature control.
- Automatic lidding film feed.
- Power supply 220/230 V · 50/60 Hz, 600 W.
- Options: gas flushing and perimeter film trimming.

KEY DATA

Max. tray	260 × 195 mm	Depth	120 mm	Power	600 W
Film width	200 mm	Max. reel	Ø 230 mm	Net weight	33 kg

MODELS AND DIMENSIONS

REF.	CONFIGURATION	DIMENSIONS (MM)	SUITABLE FOR
TSRPS200	RPS200 · 9 programs	255 × 380 × 490	Trays up to 205 × 165 mm
TSRPS220	RPS220 · gas and trim options	310 × 470 × 610	Trays up to 260 × 195 mm
TSRPS380	RPS380 · gas and trim options	460 × 480 × 610	Trays up to 320 × 260 mm

Mould not included: standard fixed, standard multi-format or made to the customer's tray, on request. Multi-format for 260 × 190, 230 × 190, 192 × 136 and 136 × 96 mm trays.

APPLICATIONS

Shops, food workshops and kitchens packing in film-sealed trays that want the gas flushing option: ready meals and products ready for sale.

For information only. Specifications, dimensions and finishes may change without notice due to product improvements. The image is indicative. Please request a quotation to confirm dimensions, materials and lead times.